	<b>Evidence of Performance</b> Resistance to wind load Watertightness Air permeability	ift
	Test Report 10-001301-PB02-A01-02-en-02	ROSENHEIM
Client	BAUPLAST PAZARLAMA PLASTİK	<b>Basis</b> EN 14351-1 : 2006-03
	SAN. İÇ VE DIŞ TİC. A.Ş Bağlar mah. Osmanpaşa cad. No:21 KAT:2	Test standards: EN 1026 : 2000-06 EN 1027 : 2000-06 EN 12211 : 2000-06
	GÜNEŞLİ-BAĞCILAR/İSTANBUL Turkey	EN 12046-1 : 2003-11 EN 14609 : 2004-03 Test Report 102 42739/2e dated
		30 July 2010 Test Report 10-001301-PB02- A01-02-en-01 dated
Product	Single leaf tilt and turn casement door	9 November 2011
System	BAU 2000	Corresponds to the national standard (DIN EN)
Överall dimensions (w x H)	900 mm x 2,000 mm	Representation
Frame material	PVC-U/white	
Special features	Reinforcements mitred and mounted without cutback. Glazing rebate horizontal at bottom additional sealed with pourable sealant.	

Resistance to wind load - EN 12210



Watertightness - EN 12208



Class 8A

Air permeability - EN 12207



Class 4

ift Rosenheim 3 March 2011

Jörn Deleness, Dipl.-Ing. (Fr

Head of Testing Department **Building Components** 



ift Rosenheim GmbH Geschäftsführer: Dipl.-Ing. (FH) Ulrich Sieberath Dr. Jochen Peichl



Operating Product Officer Building Components

Theodo D-83020 rtosermenn Tel.: +49 (0)8031/261-0 Fax: +49 (0)8031/261-290 www.ift-rosenheim.de

z: 83026 Rosenheim Traunstein, HRB 14763 Sparkasse Rosenheim Kto. 3822 BLZ 711 500 00

Notified Body Nr.: 0757 Anerkannte PÜZ-Stelle: BAY 18

Notes on publication

Instruction for use

Validity

specimen.

sibility.

ageing.

an abstract.

Contents

10 pages

The present test report serves to demonstrate the above charac-

teristics of windows according to EN 14351-1:2006-03. The results obtained can be used by the

manufacturer as the basis for the manufacturer ITT test report summary. The conditions and re-

quirements set out by EN 14351-1:2006-03 shall be observed.

The data and results refer solely to the tested and described

The test results can be extrapolated as per EN 14351-1, under observance of Annex E 1., under

the manufacturer's own respon-

The test does not allow any statement to be made on further characteristics of the present structure and quality, in particular the effects of weathering and

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies. The cover sheet can be used as



The report contains a total of