Evidence of Performance

Istoc Taptancilar Carsisi 25.Ada No.: 115-117

Resistance to wind load Watertightness Air permeability Operating forces

Test Report 102 42709/1e U



Basis

EN 14351-1: 2006-03


Test standards: EN 1026 : 2000-06 EN 1027 : 2000-06 EN 12211 : 2000-06 EN 12046-1 : 2003-11 EN 14609 : 2004-03

Test report 102 41670/1e dated

8. January 2010

Corresponds to the national standard (DIN EN)

Representation



Single leaf tilt and turn casement door

BAGCILAR Mahmut Bey Istanbul

System Overall dimensions (w x H) **BAU 9100**

Turkey

Client Bauplast Pazarlama

San.Tic.A.S.

950 mm x 2,000 mm

Frame material PVC

PVC-U/white

Special features

Bracings mitred and mounted without cutback

Resistance to wind load - EN 12210



Class C5 / B5

Watertightness - EN 12208



Class E900

Air permeability – EN 12207



Class 3

Operating forces - EN 13115



Class 1

ift Rosenheim 2. March 2010

Jörn Feel Lass, Dipl.-Ing. (FH)
Head of Testing Department
ift Centre Windows & Facades

ift

ift Rosenheim GmbH

Geschäftsführer: Dipl.-Ing. (FH) Ulrich Sieberath Dr. Jochen Peichl Robert Kolacny, Dipl.-Ing. (FH)
Test engineer
ift Centre Windows & Facades

Theodor-Gietl-Str. 7 - 9 D-83026 Rosenheim Tel.: +49 (0)8031/261-0 Fax: +49 (0)8031/261-290 www.ift-rosenheim.de Sitz: 83026 Rosenheim AG Traunstein, HRB 14763 Sparkasse Rosenheim Kto. 3822 BLZ 711 500 00

Instruction for use

The present test report serves to demonstrate the above characteristics of windows according to EN 14351-1:2006-03. The results obtained can be used by the manufacturer as the basis for the manufacturer ITT test report summary. The conditions and requirements set out by EN 14351-1:2006-03 shall be observed.

Validity

The data and results refer solely to the tested and described specimen.

The test results can be extrapolated as per EN 14351-1, under observance of Annex E 1., under the manufacturer's own responsibility.

The test does not allow any statement to be made on further characteristics of the present structure and quality, in particular the effects of weathering and ageing.

Notes on publication

The **ift**-Guidance Sheet "Conditions and Guidance for the Use of **ift** Test Documents" applies.

The cover sheet can be used as an abstract.

Contents

The report contains a total of 11 pages

